

```
[root@ol6-agrac-rac1 ~]# cat /etc/sysconfig/network
NETWORKING=yes
HOSTNAME=ol6-agrac-rac1.localdomain
[root@ol6-agrac-rac1 ~]# uname -a
Linux ol6-agrac-rac1.localdomain 3.8.13-16.2.1.el6uek.x86_64 #1 SMP Thu Nov 7 17:01:44
PST 2013 x86_64 x86_64 x86_64 GNU/Linux
[root@ol6-agrac-rac1 ~]# █
```

File Edit View Search Terminal Help

```
[root@ol6-agrac-rac1 ~]# cat /etc/hosts
127.0.0.1    localhost localhost.localdomain localhost4 localhost4.localdomain4
::1        localhost localhost.localdomain localhost6 localhost6.localdomain6
192.168.0.111  ol6-agrac-rac1.localdomain    ol6-agrac-rac1
[root@ol6-agrac-rac1 ~]# gedit /etc/hosts
[root@ol6-agrac-rac1 ~]# cat /etc/hosts
127.0.0.1    localhost localhost.localdomain localhost4 localhost4.localdomain4
::1        localhost localhost.localdomain localhost6 localhost6.localdomain6
# Public
192.168.0.111  ol6-agrac-rac1.localdomain    ol6-agrac-rac1
192.168.0.112  ol6-agrac-rac2.localdomain    ol6-agrac-rac2
# Private
192.168.1.111  ol6-agrac-rac1-priv.localdomain    ol6-agrac-rac1-priv
192.168.1.112  ol6-agrac-rac2-priv.localdomain    ol6-agrac-rac2-priv
# Virtual
192.168.0.113  ol6-agrac-rac1-vip.localdomain    ol6-agrac-rac1-vip
192.168.0.114  ol6-agrac-rac2-vip.localdomain    ol6-agrac-rac2-vip
# SCAN
192.168.0.115  ol6-agrac-scan.localdomain    ol6-agrac-scan
192.168.0.116  ol6-agrac-scan.localdomain    ol6-agrac-scan
192.168.0.117  ol6-agrac-scan.localdomain    ol6-agrac-scan

[root@ol6-agrac-rac1 ~]#
```

Network Connections



Name	Last Used
▼ Wired	
System eth0	2 minutes ago
Auto eth3	2 hours ago

Network Connections

Name	Last Used
Wired	
eth0	4 minutes ago
eth1	2 hours ago

Add

Edit

Delete

Close

Editing eth0

Connection name:

Connect automatically
 Available to all users

Wired 802.1x Security **IPv4 Settings** IPv6 Settings

Method:

Addresses

Address	Netmask	Gateway	
192.168.0.111	255.255.255.0	192.168.0.1	<input type="button" value="Add"/>
			<input type="button" value="Delete"/>

DNS servers:

Search domains:

DHCP client ID:

Require IPv4 addressing for this connection to complete

```
root@ol6-agrac-rac1:~  
File Edit View Search Terminal Help  
[root@ol6-agrac-rac1 ~]# gedit /etc/hosts  
[root@ol6-agrac-rac1 ~]# cat /etc/hosts  
127.0.0.1    localhost localhost.localdomain localhost4 localhost4.local  
::1        localhost localhost.localdomain localhost6 localhost6.local  
# Public  
192.168.0.111  ol6-agrac-rac1.localdomain    ol6-agrac-rac1  
192.168.0.112  ol6-agrac-rac2.localdomain    ol6-agrac-rac2  
# Private  
192.168.1.111  ol6-agrac-rac1-priv.localdomain ol6-agrac-rac1-priv  
192.168.1.112  ol6-agrac-rac2-priv.localdomain ol6-agrac-rac2-priv  
# Virtual  
192.168.0.113  ol6-agrac-rac1-vip.localdomain ol6-agrac-rac1-vip  
192.168.0.114  ol6-agrac-rac2-vip.localdomain ol6-agrac-rac2-vip  
# SCAN  
192.168.0.115  ol6-agrac-scan.localdomain    ol6-agrac-scan  
192.168.0.116  ol6-agrac-scan.localdomain    ol6-agrac-scan  
192.168.0.117  ol6-agrac-scan.localdomain    ol6-agrac-scan  
[root@ol6-agrac-rac1 ~]#
```

Editing eth0

Connection name:

Connect automatically
 Available to all users

Wired | 802.1x Security | IPv4 Settings | **IPv6 Settings**

Method:

Addresses

Address	Prefix	Gateway
<input type="text"/>		

DNS servers:

Search domains:

Require IPv6 addressing for this connection to complete

```
root@ol6-agrac-rac1:~  
File Edit View Search Terminal Help  
[root@ol6-agrac-rac1 ~]# gedit /etc/hosts  
[root@ol6-agrac-rac1 ~]# cat /etc/hosts  
127.0.0.1    localhost localhost.localdomain localhost4 localhost4.local  
::1        localhost localhost.localdomain localhost6 localhost6.local  
# Public  
192.168.0.111  ol6-agrac-rac1.localdomain    ol6-agrac-rac1  
192.168.0.112  ol6-agrac-rac2.localdomain    ol6-agrac-rac2  
# Private  
192.168.1.111  ol6-agrac-rac1-priv.localdomain ol6-agrac-rac1-priv  
192.168.1.112  ol6-agrac-rac2-priv.localdomain ol6-agrac-rac2-priv  
# Virtual  
192.168.0.113  ol6-agrac-rac1-vip.localdomain ol6-agrac-rac1-vip  
192.168.0.114  ol6-agrac-rac2-vip.localdomain ol6-agrac-rac2-vip  
# SCAN  
192.168.0.115  ol6-agrac-scan.localdomain    ol6-agrac-scan  
192.168.0.116  ol6-agrac-scan.localdomain    ol6-agrac-scan  
192.168.0.117  ol6-agrac-scan.localdomain    ol6-agrac-scan  
  
[root@ol6-agrac-rac1 ~]#
```

Editing eth1

Connection name:

Connect automatically
 Available to all users

Wired 802.1x Security **IPv4 Settings** IPv6 Settings

Method:

Addresses

Address	Netmask	Gateway	
192.168.1.111	255.255.255.0	0.0.0.0	<input type="button" value="Add"/>
			<input type="button" value="Delete"/>

DNS servers:

Search domains:

DHCP client ID:

Require IPv4 addressing for this connection to complete

```
root@ol6-agrac-rac1:~  
File Edit View Search Terminal Help  
[root@ol6-agrac-rac1 ~]# gedit /etc/hosts  
[root@ol6-agrac-rac1 ~]# cat /etc/hosts  
127.0.0.1    localhost localhost.localdomain localhost4 localhost4.local  
::1        localhost localhost.localdomain localhost6 localhost6.local  
# Public  
192.168.0.111  ol6-agrac-rac1.localdomain  ol6-agrac-rac1  
192.168.0.112  ol6-agrac-rac2.localdomain  ol6-agrac-rac2  
# Private  
192.168.1.111  ol6-agrac-rac1-priv.localdomain  ol6-agrac-rac1-priv  
192.168.1.112  ol6-agrac-rac2-priv.localdomain  ol6-agrac-rac2-priv  
# Virtual  
192.168.0.113  ol6-agrac-rac1-vip.localdomain  ol6-agrac-rac1-vip  
192.168.0.114  ol6-agrac-rac2-vip.localdomain  ol6-agrac-rac2-vip  
# SCAN  
192.168.0.115  ol6-agrac-scan.localdomain  ol6-agrac-scan  
192.168.0.116  ol6-agrac-scan.localdomain  ol6-agrac-scan  
192.168.0.117  ol6-agrac-scan.localdomain  ol6-agrac-scan  
  
[root@ol6-agrac-rac1 ~]#
```

Editing eth1

Connection name:

Connect automatically
 Available to all users

Wired | 802.1x Security | IPv4 Settings | **IPv6 Settings**

Method:

Addresses

Address	Prefix	Gateway
<input type="text"/>		

DNS servers:

Search domains:

Require IPv6 addressing for this connection to complete

```
root@ol6-agrac-rac1:~  
File Edit View Search Terminal Help  
[root@ol6-agrac-rac1 ~]# gedit /etc/hosts  
[root@ol6-agrac-rac1 ~]# cat /etc/hosts  
127.0.0.1    localhost localhost.localdomain localhost4 localhost4.localhost4.localdomain4  
:::1       localhost localhost.localdomain localhost6 localhost6.localdomain6  
# Public  
192.168.0.111 ol6-agrac-rac1.localdomain ol6-agrac-rac1  
192.168.0.112 ol6-agrac-rac2.localdomain ol6-agrac-rac2  
# Private  

```



```
[root@ol6-agrac-racl ~]# uname -a
Linux ol6-agrac-racl.localdomain 3.8.13-16.2.1.el6uek.x86_64 #1 SMP Th
u Nov 7 17:01:44 PST 2013 x86_64 x86_64 x86_64 GNU/Linux
[root@ol6-agrac-racl ~]# ping ol6-agrac-racl
PING ol6-agrac-racl.localdomain (192.168.0.111) 56(84) bytes of data.
64 bytes from ol6-agrac-racl.localdomain (192.168.0.111): icmp_seq=1 t
tl=64 time=0.031 ms
64 bytes from ol6-agrac-racl.localdomain (192.168.0.111): icmp_seq=2 t
tl=64 time=0.044 ms
64 bytes from ol6-agrac-racl.localdomain (192.168.0.111): icmp_seq=3 t
tl=64 time=0.049 ms
^C
--- ol6-agrac-racl.localdomain ping statistics ---
3 packets transmitted, 3 received, 0% packet loss, time 2152ms
rtt min/avg/max/mdev = 0.031/0.041/0.049/0.009 ms
[root@ol6-agrac-racl ~]# ping ol6-agrac-racl-priv
PING ol6-agrac-racl-priv.localdomain (192.168.1.111) 56(84) bytes of d
ata.
64 bytes from ol6-agrac-racl-priv.localdomain (192.168.1.111): icmp_se
q=1 ttl=64 time=0.033 ms
64 bytes from ol6-agrac-racl-priv.localdomain (192.168.1.111): icmp_se
q=2 ttl=64 time=0.036 ms
64 bytes from ol6-agrac-racl-priv.localdomain (192.168.1.111): icmp_se
q=3 ttl=64 time=0.050 ms
^C
--- ol6-agrac-racl-priv.localdomain ping statistics ---
3 packets transmitted, 3 received, 0% packet loss, time 2699ms
rtt min/avg/max/mdev = 0.033/0.039/0.050/0.010 ms
[root@ol6-agrac-racl ~]# █
```

```
[root@ol6-agrac-rac1 ~]# ifconfig -a | grep eth
eth0      Link encap:Ethernet  HWaddr 00:0C:29:C5:AA:43
eth1      Link encap:Ethernet  HWaddr 00:0C:29:C5:AA:4D
[root@ol6-agrac-rac1 ~]# ls -la /etc/sysconfig/network-scripts
total 224
drwxr-xr-x. 2 root root 4096 Jan 19 21:11 .
drwxr-xr-x. 8 root root 4096 Jan 21 14:39 ..
-rw-r--r--. 1 root root 275 Jan 20 00:13 ifcfg-eth0
-rw-r--r--. 1 root root 271 Jan 19 21:06 ifcfg-eth0~
-rw-r--r--. 1 root root 255 Jan 19 21:11 ifcfg-eth1
-rw-r--r--. 1 root root 251 Jan 19 21:07 ifcfg-eth1~
-rw-r--r--. 1 root root 254 Oct 10 2013 ifcfg-lo
lrwxrwxrwx. 1 root root 20 Nov 4 14:28 ifdown -> ../../../../sbin/ifdown
-rwxr-xr-x. 1 root root 627 Oct 10 2013 ifdown-bnep
-rwxr-xr-x. 1 root root 5430 Oct 10 2013 ifdown-eth
-rwxr-xr-x. 1 root root 781 Oct 10 2013 ifdown-ipp
-rwxr-xr-x. 1 root root 4168 Oct 10 2013 ifdown-ipv6
lrwxrwxrwx. 1 root root 11 Nov 4 14:28 ifdown-isdn -> ifdown-ipp
-rwxr-xr-x. 1 root root 1481 Oct 10 2013 ifdown-post
-rwxr-xr-x. 1 root root 1064 Oct 10 2013 ifdown-ppp
-rwxr-xr-x. 1 root root 835 Oct 10 2013 ifdown-routes
-rwxr-xr-x. 1 root root 1465 Oct 10 2013 ifdown-sit
-rwxr-xr-x. 1 root root 1434 Oct 10 2013 ifdown-tunnel
lrwxrwxrwx. 1 root root 18 Nov 4 14:28 ifup -> ../../../../sbin/ifup
-rwxr-xr-x. 1 root root 12444 Oct 10 2013 ifup-aliases
-rwxr-xr-x. 1 root root 859 Oct 10 2013 ifup-bnep
-rwxr-xr-x. 1 root root 10556 Oct 10 2013 ifup-eth
-rwxr-xr-x. 1 root root 11971 Oct 10 2013 ifup-ipp
-rwxr-xr-x. 1 root root 10490 Oct 10 2013 ifup-ipv6
lrwxrwxrwx. 1 root root 9 Nov 4 14:28 ifup-isdn -> ifup-ipp
-rwxr-xr-x. 1 root root 727 Oct 10 2013 ifup-plip
-rwxr-xr-x. 1 root root 954 Oct 10 2013 ifup-plusb
-rwxr-xr-x. 1 root root 2364 Oct 10 2013 ifup-post
-rwxr-xr-x. 1 root root 4154 Oct 10 2013 ifup-ppp
-rwxr-xr-x. 1 root root 1930 Nov 22 2013 ifup-routes
-rwxr-xr-x. 1 root root 3289 Oct 10 2013 ifup-sit
-rwxr-xr-x. 1 root root 2488 Oct 10 2013 ifup-tunnel
-rwxr-xr-x. 1 root root 3770 Oct 10 2013 ifup-wireless
-rwxr-xr-x. 1 root root 4623 Oct 10 2013 init.ipv6-global
-rwxr-xr-x. 1 root root 1125 Oct 10 2013 net.hotplug
-rw-r--r--. 1 root root 13386 Oct 10 2013 network-functions
-rw-r--r--. 1 root root 29853 Oct 10 2013 network-functions-ipv6
[root@ol6-agrac-rac1 ~]#
```

```
[root@ol6-agrac-rac1 ~]# cat /etc/sysconfig/network-scripts/ifcfg-eth0
TYPE=Ethernet
BOOTPROTO=none
IPADDR=192.168.0.111
PREFIX=24
GATEWAY=192.168.0.1
DNS1=192.168.0.111
DEFROUTE=yes
IPV4_FAILURE_FATAL=yes
IPV6INIT=no
DEVICE="eth0"
NAME="eth0"
UUID=f7d3ec7e-34ab-4b05-86c8-c69b0587da0a
ONBOOT=yes
HWADDR=00:0C:29:C5:AA:43
LAST_CONNECT=1484867421
[root@ol6-agrac-rac1 ~]# cat /etc/sysconfig/network-scripts/ifcfg-eth1
TYPE=Ethernet
BOOTPROTO=none
DEFROUTE=yes
IPV4_FAILURE_FATAL=yes
IPV6INIT=no
DEVICE="eth1"
NAME="eth1"
UUID=fd35275e-1e33-448c-ala9-ea69d66ee27c
ONBOOT=yes
HWADDR=00:0C:29:C5:AA:4D
IPADDR=192.168.1.111
PREFIX=24
DNS1=192.168.0.111
LAST_CONNECT=1484816613
[root@ol6-agrac-rac1 ~]#
```

File Edit View Search Terminal Help

```
[root@ol6-agrac-rac2 ~]# cat /etc/sysconfig/network
```

```
NETWORKING=yes
```

```
HOSTNAME=ol6-agrac-rac2.localdomain
```

```
[root@ol6-agrac-rac2 ~]# uname -a
```

```
Linux ol6-agrac-rac2.localdomain 3.8.13-16.2.1.el6uek.x86_64 #1 SMP Thu Nov 7 17:01:44 PST 2013 x86_64 x86_64 x86_64 GNU/Linux
```

```
[root@ol6-agrac-rac2 ~]# cat /etc/hosts
```

```
127.0.0.1    localhost localhost.localdomain localhost4 localhost4.localdomain4
::1         localhost localhost.localdomain localhost6 localhost6.localdomain6
```

```
# Public
```

```
192.168.0.111 ol6-agrac-rac1.localdomain ol6-agrac-rac1
```

```
192.168.0.112 ol6-agrac-rac2.localdomain ol6-agrac-rac2
```

```
# Private
```

```
192.168.1.111 ol6-agrac-rac1-priv.localdomain ol6-agrac-rac1-priv
```

```
192.168.1.112 ol6-agrac-rac2-priv.localdomain ol6-agrac-rac2-priv
```

```
# Virtual
```

```
192.168.0.113 ol6-agrac-rac1-vip.localdomain ol6-agrac-rac1-vip
```

```
192.168.0.114 ol6-agrac-rac2-vip.localdomain ol6-agrac-rac2-vip
```

```
# SCAN
```

```
192.168.0.115 ol6-agrac-scan.localdomain ol6-agrac-scan
```

```
192.168.0.116 ol6-agrac-scan.localdomain ol6-agrac-scan
```

```
192.168.0.117 ol6-agrac-scan.localdomain ol6-agrac-scan
```

```
[root@ol6-agrac-rac2 ~]#
```

Network Connections

Name	Last Used
▼ Wired	
System eth0	now
Auto eth2	10 minutes ago

Add

Edit

Delete

Close

Network Connections

Name	Last Used
▼ Wired	
eth0	1 minute ago
eth1	12 minutes ago

Add

Edit

Delete

Close

Editing eth0

Connection name:

Connect automatically
 Available to all users

Wired | 802.1x Security | **IPv4 Settings** | IPv6 Settings

Method:

Addresses

Address	Netmask	Gateway	
192.168.0.112	255.255.255.0	192.168.0.1	<input type="button" value="Add"/>
			<input type="button" value="Delete"/>

DNS servers:

Search domains:

DHCP client ID:

Require IPv4 addressing for this connection to complete

Network Connections

Name	Last Used	
▼ Wired		
eth0	1 minute ago	<input type="button" value="Add"/>
eth1	12 minutes ago	<input type="button" value="Edit..."/>
		<input type="button" value="Delete..."/>

Editing eth0

Connection name:

Connect automatically
 Available to all users

Wired | 802.1x Security | IPv4 Settings | **IPv6 Settings**

Method:

Addresses

Address	Prefix	Gateway

DNS servers:

Search domains:

Require IPv6 addressing for this connection to complete

Network Connections

Name	Last Used
▼ Wired	
eth0	1 minute ago
eth1	12 minutes ago

Editing eth1

Connection name:

Connect automatically
 Available to all users

Wired | 802.1x Security | **IPv4 Settings** | IPv6 Settings

Method:

Addresses

Address	Netmask	Gateway
192.168.1.112	255.255.255.0	0.0.0.0

DNS servers:

Search domains:

DHCP client ID:

Require IPv4 addressing for this connection to complete

Network Connections

Name	Last Used
Wired	
eth0	4 minutes ago
eth1	12 minutes ago

Editing eth1

Connection name:

Connect automatically
 Available to all users

Wired | 802.1x Security | IPv4 Settings | **IPv6 Settings**

Method:

Addresses

Address	Prefix	Gateway
<input type="text"/>		

DNS servers:

Search domains:

Require IPv6 addressing for this connection to complete

Network Connections

Name	Last Used
Wired	
eth0	4 minutes ago
eth1	12 minutes ago

File Edit View Search Tools Documents Help

 Open Save Print Undo Redo Cut Copy Paste Find Help

hosts

```
127.0.0.1 localhost localhost.localdomain localhost4 localhost4.localdomain4
::1 localhost localhost.localdomain localhost6 localhost6.localdomain6
# Public
192.168.0.111 ol6-agrac-rac1.localdomain ol6-agrac-rac1
192.168.0.112 ol6-agrac-rac2.localdomain ol6-agrac-rac2
# Private
192.168.1.111 ol6-agrac-rac1-priv.localdomain ol6-agrac-rac1-priv
192.168.1.112 ol6-agrac-rac2-priv.localdomain ol6-agrac-rac2-priv
# Virtual
192.168.0.113 ol6-agrac-rac1-vip.localdomain ol6-agrac-rac1-vip
192.168.0.114 ol6-agrac-rac2-vip.localdomain ol6-agrac-rac2-vip
# SCAN
192.168.0.115 ol6-agrac-scan.localdomain ol6-agrac-scan
192.168.0.116 ol6-agrac-scan.localdomain ol6-agrac-scan
192.168.0.117 ol6-agrac-scan.localdomain ol6-agrac-scan
```

```
[root@ol6-agrac-rac2 rac1]# uname -a
Linux ol6-agrac-rac2.localdomain 3.8.13-16.2.1.el6uek.x86_64 #1 SMP Thu Nov 7 17:01:44 PST 2013 x86_64 x86_64 x86_64 GNU/Linux
[root@ol6-agrac-rac2 rac1]# ping ol6-agrac-rac2
PING ol6-agrac-rac2.localdomain (192.168.0.112) 56(84) bytes of data:
64 bytes from ol6-agrac-rac2.localdomain (192.168.0.112): icmp_seq=1 ttl=64 time=0.055 ms
64 bytes from ol6-agrac-rac2.localdomain (192.168.0.112): icmp_seq=2 ttl=64 time=0.040 ms
^C
--- ol6-agrac-rac2.localdomain ping statistics ---
2 packets transmitted, 2 received, 0% packet loss, time 1370ms
rtt min/avg/max/mdev = 0.040/0.047/0.055/0.010 ms
[root@ol6-agrac-rac2 rac1]# ping ol6-agrac-rac1
PING ol6-agrac-rac1.localdomain (192.168.0.111) 56(84) bytes of data:
64 bytes from ol6-agrac-rac1.localdomain (192.168.0.111): icmp_seq=1 ttl=64 time=0.464 ms
64 bytes from ol6-agrac-rac1.localdomain (192.168.0.111): icmp_seq=2 ttl=64 time=0.358 ms
^C
--- ol6-agrac-rac1.localdomain ping statistics ---
2 packets transmitted, 2 received, 0% packet loss, time 1496ms
rtt min/avg/max/mdev = 0.358/0.411/0.464/0.053 ms
[root@ol6-agrac-rac2 rac1]# ping ol6-agrac-rac1-priv
PING ol6-agrac-rac1-priv.localdomain (192.168.1.111) 56(84) bytes of data:
64 bytes from ol6-agrac-rac1-priv.localdomain (192.168.1.111): icmp_seq=1 ttl=64 time=0.456 ms
64 bytes from ol6-agrac-rac1-priv.localdomain (192.168.1.111): icmp_seq=2 ttl=64 time=0.257 ms
^C
--- ol6-agrac-rac1-priv.localdomain ping statistics ---
2 packets transmitted, 2 received, 0% packet loss, time 1605ms
rtt min/avg/max/mdev = 0.257/0.356/0.456/0.101 ms
[root@ol6-agrac-rac2 rac1]# ping ol6-agrac-rac2-priv
PING ol6-agrac-rac2-priv.localdomain (192.168.1.112) 56(84) bytes of data:
64 bytes from ol6-agrac-rac2-priv.localdomain (192.168.1.112): icmp_seq=1 ttl=64 time=0.033 ms
64 bytes from ol6-agrac-rac2-priv.localdomain (192.168.1.112): icmp_seq=2 ttl=64 time=0.033 ms
```

```
[root@ol6-agrac-rac1 ~]# uname -a
Linux ol6-agrac-rac1.localdomain 3.8.13-16.2.1.el6uek.x86_64 #1 SMP Thu Nov 7 17:01:44 PST 2013 x86_64 x86_64 x86_64 GNU/Linux
[root@ol6-agrac-rac1 ~]# ping ol6-agrac-rac1
PING ol6-agrac-rac1.localdomain (192.168.0.111) 56(84) bytes of data.
64 bytes from ol6-agrac-rac1.localdomain (192.168.0.111): icmp_seq=1 ttl=64 time=0.029 ms
64 bytes from ol6-agrac-rac1.localdomain (192.168.0.111): icmp_seq=2 ttl=64 time=0.045 ms
^C
--- ol6-agrac-rac1.localdomain ping statistics ---
2 packets transmitted, 2 received, 0% packet loss, time 1105ms
rtt min/avg/max/mdev = 0.029/0.037/0.045/0.008 ms
[root@ol6-agrac-rac1 ~]# ping ol6-agrac-rac2
PING ol6-agrac-rac2.localdomain (192.168.0.112) 56(84) bytes of data.
64 bytes from ol6-agrac-rac2.localdomain (192.168.0.112): icmp_seq=1 ttl=64 time=0.478 ms
64 bytes from ol6-agrac-rac2.localdomain (192.168.0.112): icmp_seq=2 ttl=64 time=0.253 ms
^C
--- ol6-agrac-rac2.localdomain ping statistics ---
2 packets transmitted, 2 received, 0% packet loss, time 1949ms
rtt min/avg/max/mdev = 0.253/0.365/0.478/0.114 ms
[root@ol6-agrac-rac1 ~]# ping ol6-agrac-rac1-priv
PING ol6-agrac-rac1-priv.localdomain (192.168.1.111) 56(84) bytes of data.
64 bytes from ol6-agrac-rac1-priv.localdomain (192.168.1.111): icmp_seq=1 ttl=64 time=0.035 ms
64 bytes from ol6-agrac-rac1-priv.localdomain (192.168.1.111): icmp_seq=2 ttl=64 time=0.041 ms
^C
--- ol6-agrac-rac1-priv.localdomain ping statistics ---
2 packets transmitted, 2 received, 0% packet loss, time 1558ms
rtt min/avg/max/mdev = 0.035/0.038/0.041/0.003 ms
[root@ol6-agrac-rac1 ~]# ping ol6-agrac-rac2-priv
PING ol6-agrac-rac2-priv.localdomain (192.168.1.112) 56(84) bytes of data.
64 bytes from ol6-agrac-rac2-priv.localdomain (192.168.1.112): icmp_seq=1 ttl=64 time=0.396 ms
64 bytes from ol6-agrac-rac2-priv.localdomain (192.168.1.112): icmp_seq=2 ttl=64 time=0.198 ms
^C
--- ol6-agrac-rac2-priv.localdomain ping statistics ---
2 packets transmitted, 2 received, 0% packet loss, time 1886ms
rtt min/avg/max/mdev = 0.198/0.297/0.396/0.099 ms
[root@ol6-agrac-rac1 ~]#
```

```
[root@ol6-agrac-rac2 ~]# ifconfig -a | grep eth
eth0      Link encap:Ethernet  HWaddr 00:0C:29:28:88:E6
eth1      Link encap:Ethernet  HWaddr 00:0C:29:28:88:F0
[root@ol6-agrac-rac2 ~]# ls -la /etc/sysconfig/network-scripts
total 224
drwxr-xr-x. 2 root root 4096 Jan 19 21:53 .
drwxr-xr-x. 8 root root 4096 Dec 14 17:42 ..
-rw-r--r--. 1 root root 275 Jan 19 21:52 ifcfg-eth0
-rw-r--r--. 1 root root 259 Jan 19 12:43 ifcfg-eth0~
-rw-r--r--. 1 root root 255 Jan 19 21:53 ifcfg-eth1
-rw-r--r--. 1 root root 239 Jan 19 12:49 ifcfg-eth1~
-rw-r--r--. 1 root root 254 Oct 10 2013 ifcfg-lo
lrwxrwxrwx. 1 root root 20 Nov 4 14:28 ifdown -> ../../../../sbin/ifdown
-rwxr-xr-x. 1 root root 627 Oct 10 2013 ifdown-bnep
-rwxr-xr-x. 1 root root 5430 Oct 10 2013 ifdown-eth
-rwxr-xr-x. 1 root root 781 Oct 10 2013 ifdown-ipp
-rwxr-xr-x. 1 root root 4168 Oct 10 2013 ifdown-ipv6
lrwxrwxrwx. 1 root root 11 Nov 4 14:28 ifdown-isdn -> ifdown-ipp
-rwxr-xr-x. 1 root root 1481 Oct 10 2013 ifdown-post
-rwxr-xr-x. 1 root root 1064 Oct 10 2013 ifdown-ppp
-rwxr-xr-x. 1 root root 835 Oct 10 2013 ifdown-routes
-rwxr-xr-x. 1 root root 1465 Oct 10 2013 ifdown-sit
-rwxr-xr-x. 1 root root 1434 Oct 10 2013 ifdown-tunnel
lrwxrwxrwx. 1 root root 18 Nov 4 14:28 ifup -> ../../../../sbin/ifup
-rwxr-xr-x. 1 root root 12444 Oct 10 2013 ifup-aliases
-rwxr-xr-x. 1 root root 859 Oct 10 2013 ifup-bnep
-rwxr-xr-x. 1 root root 10556 Oct 10 2013 ifup-eth
-rwxr-xr-x. 1 root root 11971 Oct 10 2013 ifup-ipp
-rwxr-xr-x. 1 root root 10490 Oct 10 2013 ifup-ipv6
lrwxrwxrwx. 1 root root 9 Nov 4 14:28 ifup-isdn -> ifup-ipp
-rwxr-xr-x. 1 root root 727 Oct 10 2013 ifup-plip
-rwxr-xr-x. 1 root root 954 Oct 10 2013 ifup-plusb
-rwxr-xr-x. 1 root root 2364 Oct 10 2013 ifup-post
-rwxr-xr-x. 1 root root 4154 Oct 10 2013 ifup-ppp
-rwxr-xr-x. 1 root root 1930 Nov 22 2013 ifup-routes
-rwxr-xr-x. 1 root root 3289 Oct 10 2013 ifup-sit
-rwxr-xr-x. 1 root root 2488 Oct 10 2013 ifup-tunnel
-rwxr-xr-x. 1 root root 3770 Oct 10 2013 ifup-wireless
-rwxr-xr-x. 1 root root 4623 Oct 10 2013 init.ipv6-global
-rwxr-xr-x. 1 root root 1125 Oct 10 2013 net.hotplug
-rw-r--r--. 1 root root 13386 Oct 10 2013 network-functions
-rw-r--r--. 1 root root 29853 Oct 10 2013 network-functions-ipv6
[root@ol6-agrac-rac2 ~]#
```

```
[root@ol6-agrac-rac2 ~]# cat /etc/sysconfig/network-scripts/ifcfg-eth0
TYPE=Ethernet
BOOTPROTO=none
IPADDR=192.168.0.112
PREFIX=24
GATEWAY=192.168.0.1
DNS1=192.168.0.111
DEFROUTE=yes
IPV4_FAILURE_FATAL=yes
IPV6INIT=no
DEVICE="eth0"
NAME="eth0"
UUID=354c406a-66dc-4e1c-bbee-5c1d9952ffd1
ONBOOT=yes
HWADDR=00:0C:29:28:88:E6
LAST_CONNECT=1484825976
[root@ol6-agrac-rac2 ~]# cat /etc/sysconfig/network-scripts/ifcfg-eth1
TYPE=Ethernet
BOOTPROTO=none
DEFROUTE=yes
IPV4_FAILURE_FATAL=yes
IPV6INIT=no
DEVICE="eth1"
NAME="eth1"
UUID=7e6077d1-f92c-4dfe-a954-33e0f79ffb72
ONBOOT=yes
HWADDR=00:0C:29:28:88:F0
IPADDR=192.168.1.112
PREFIX=24
DNS1=192.168.0.111
LAST_CONNECT=1484825376
[root@ol6-agrac-rac2 ~]# █
```